

KLIKK HET EN ZIE

Sollicitatie



Belangrijkste kenmerken

- Voor stabiele prestaties: controller met twee inverters, uitbreidbaar PLC-systeem, zelfuitvaldiagnose, dubbele encoder.
- Voor eenvoudige bediening: touchscreen monitor, onafhankelijke temperatuur PID-regelaar,
- Voor aanpassingsvermogen: één set machines kan worden toegepast op verschillende soorten producten via optionele apparaten, zoals luchtvlapparaat, voerlijn, etc.

Hoofd motor

Item	DS-320L	DS-420L	DS-520L	DS-720L
Measuring Range	150 ~ 150ml	150-1500ml	150~2000mL	150~4000ml
Packaging Speed	5 ~ 70 bags/min	5-60 bags/min	10~50 bags/min	10~40 bags/min
Bag Width	50 ~ 150mm	60-200mm	80~250mm	100-350mm
Bag Length	80 ~ 240mm	80-300mm	80~350mm	100~450mm
Film Roll Width	Max.320mm	Max.420mm	Max:520mm	Max:720mm
Film Thickness	0.04-0.08mm			
Machine Size	(L)1185 x (W)935 x (H)1245mm	(L)1217 x (W)1015 x (H)1343mm	(L)1488*(W)1080*(H)1 490mm	(L)1716*(W)1260*(H)1 820mm
Weight	550KG	650KG	750KG	900KG
Power	220V, 50/60HZ, 2KVA	220V, 50/60HZ,	220V, 50/60HZ, 3KVA	220V, 50/60HZ,
Optional Device	Date Coder / Air-filling Device / Punching Device			
Machine Packing	Wooden Box			



Kopje meten



Platform ondersteunen

ITEM	Supporting Platform
Measurement	L)1800* W)1800* H)1800~2000mm
Material	304 stainless steel or carbon steel



Productlift met enkele bak





Production Process



Feeding



Weight measurement



Into the bag



finished product



Cutting and sealing



Longitudinal sealing

Afwerking van metaal



same 304# stainless steel material, Our Dession,
offer you 360 different surface treatment

Pakket



Ons team



Bevroren Groente Verpakkingsmachine Voor Kleine Bevroren Plant Verpakking